KLONER3D[®]240 OFFICE SERIES 3D PRINTER





Depending on the print head. KLONER3D® 3D PRINTERS MADE ENTIRELY IN ITALY

TECHNICAL SPECIFICATIONS

EXTERNAL DIMENSIONS (WxDxH)

WEIGHT

PRINT AREA (XYZ)

INTERCHANGEABLE HEAD

DUAL EXTRUDER

FILAMENT DIAMETER

NOZZLE DIAMETER

MIN. LAYER HEIGHT

HEATED PRINTER BED

CLOSED PRINTING ENVIRONMENT

PRINTER BED ADJUSTMENT

MECHANICAL MOVEMENT

MOVEMENT RESOLUTION

POSITIONING RESOLUTION

BACKLASH CONTROL

MECHANICAL ADJUSTMENT, MAINTENANCE,

LUBRICATION ETC.

PRINTABLE MATERIALS

OPERATING SYSTEM OF THE CUSTOMER

INPUT FILE FORMATS

OPERATING REQUIREMENTS

400x460x600mm

23Kg

220x240x140mm (7,40 lt)

YES

NO

3mm-1,75mm*

0,5 (0,3*-0,8*)mm

0.035*-0.05mm

YES

YES

NO

TBMS

0,01mm

0.01mm

YES

NO

MULTIMATERIAL

Windows, Mac and Linux

STL, OBJ, GCODE

elettrical: 100-240 Vac 50-60 Hz; ~280W

operation: temperature: 15°C-35°C; humidity: 15%-55%

CASE COLOR



For further information:

KLONER3D

firenze - italy tel. +39(0)55 66 43 96 fax. +39(0)55 398 0810 www.kloner3d.com info@kloner3d.com sales@kloner3d.com designed by: clevertek & Al info@clevertek.eu produced by: officine verdelli tel. +39(0)55660592